

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
28 July 2005 (28.07.2005)

PCT

(10) International Publication Number  
**WO 2005/069286 A1**

(51) International Patent Classification<sup>7</sup>: **G11B 7/125**,  
7/0045, 7/006

(21) International Application Number:  
PCT/IB2005/050124

(22) International Filing Date: 11 January 2005 (11.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0400662.3 13 January 2004 (13.01.2004) GB

(71) Applicant (for all designated States except US): **KONIN-  
KLJKE PHILIPS ELECTRONICS N.V.** [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HAROLD-BARRY,**


**John, A.** [GB/GB]; c/o Philips Intellectual Property, &  
Standards, Cross Oak Lane, Redhill Surrey RH1 5HA  
(GB). **WU, Xinyan** [CN/GB]; c/o Philips Intellectual  
Property, & Standards, Cross Oak Lane, Redhill Surrey  
RH1 5HA (GB).

(74) Agents: **WILLIAMSON, Paul, L.** et al.; c/o Philips In-  
tellectual Property, & Standards, Cross Oak Lane, Redhill  
Surrey RH1 5HA (GB).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR CONTROL OF A WRITE SIGNAL IN AN OPTICAL DISC SYSTEM



(57) Abstract: The present invention provides for an apparatus and method of controlling writing a signal to an optical disc in an optical disc system and including the step of generating a feedback signal to dynamically tune the signal output from a laser source, and including generating a plurality of timing signals serving to define a plurality of sampling windows for selecting data samples from RF signals derived from a signal reflected from the disc, generating a plurality of runlength selection signals to allow for measurement of light reflection at required runlength lands or pits, and measuring light reflected at a runlength land or pit in processing means and employing the measured signal as the said feedback signal for the said tuning of the signal source.



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*